



FLOOR STANDING CONDENSING BOILERS

MACF COMBI MAHF HEATING

with ARTIFICIAL INTELLIGENCE [AI]

[AI] CONTROL

Self-Monitoring
Self-Adjusting
Self-Commissioning
(Simply press two buttons to set up combustion)



MACF-150

MAHF-125

- Adjusts for LP or Natural Gas - **NO** Field Conversion Kits
- Built-In Primary/Secondary LABOR SAVER™ Manifold
- 7:1 Turndown Modulation Ratio in DHW Mode
- 5.7:1 Turndown Modulation Ratio in Heating Mode
- **Warranty Coverage**
-FREE 2-Year Parts & Labor Limited Warranty*
-10-Year Limited Heat Exchanger
- **Built by American Craftsman**

SMARTER & EASIER 95% AFUE EFFICIENCY

Everyone enjoys the comfort

→ **Homeowners** enjoy comfort, energy savings, and lower utility bills.

→ **Contractors** enjoy the ease of replacing boilers with floor standing condensing.



PRODUCT SPECIFICATIONS

IN DOMESTIC HOT WATER MODE

MODEL	INPUT MBH		FLOW RATE <small>(Based on 70° Temperate rise)</small>
	MAX	MIN	Gallons per minute
COMBI MACF-150	153	22	3.5

IN SPACE HEATING MODE

MODEL	INPUT MBH		AHRI CERTIFIED RATINGS		
	MAX	MIN	Heating Capacity MBH	Efficiency AFUE %	Net Water MBH (1)
COMBI MACF-150	125	22	113	95	98
HEAT ONLY MAHF-125	125	22	113	95	98

(1) Net Water Rating shown based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boilers for installation having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

VENT MATERIAL / SIZE In Inches (mm)

MODEL	COAXIAL (2) ID/OD	2-PIPE Polypropylene (2)	2-PIPE CPVC (2)
	COMBI MACF-150	2" / 4" (60mm / 100mm)	2" or 3" (60mm / 80mm)
HEAT ONLY MAHF-125	2" / 4" (60mm / 100mm)	2" or 3" (60mm / 80mm)	3" (80mm)

(2) Refer to IOM and vent pipe manufacturer's instructions for equivalent lengths and approved venting materials

BOILER CLEARANCES

DIMENSION	Combustible Materials (3)	Manufacturer Recommended for SERVICE (3) (4)
TOP	0" (0cm)	8-5/8" (220mm)
LEFT	1-3/4" (45mm)	12" (305mm)
RIGHT	1-3/4" (45mm)	1-3/4" (45mm)
FRONT	0" (0cm)	17-3/4" (450mm)
BACK	0" (0cm)	0" (0cm)
BOTTOM	0" (0cm)	0" (0cm)
COMBUSTION AIR/VENT PIPING	0" (0cm)	6" (160mm)

(3) Required distance measured from boiler jacket.

(4) Service, proper operation clearance recommendation.

TAKE ADVANTAGE OF
REBATES
with 95% AFUE

LEARN MORE!

www.uticaboilers.com

CERTIFICATIONS



2201 Dwyer Avenue; Utica, NY 13501
Tel. 800 253 7900
www.ecrinternational.com

All specifications subject to change without notice.
©2019 ECR International, Inc.
PN 240012693 Rev. [6/21/19]